



<b>Author</b>	EnviroSpec Verification Services
<b>Document type</b>	Green Star NZ compatibility analysis
<b>Document code</b>	ES-GSNZ-09-11f
<b>Validity</b>	Updated on 03/04/2014– Valid only for the following Green Star NZ tools: <ul style="list-style-type: none"> <li>- Office 2009</li> <li>- Interiors 2009</li> <li>- Education 2009</li> <li>- Industrial 2009</li> </ul>
<b>Client</b>	Forman Building Systems
<b>Product name</b>	Armstrong Fine Fissured (inc. High NRC) Ceiling Tiles
<b>Product description</b>	<p>Armstrong RH99 Fine Fissured is a medium absorption acoustic ceiling panel for suspended ceiling grid which combines a high level of acoustic absorption with exceptional impact and scratch resistant because of the factory applied paint finish over an acoustically transparent Durabrite tissue. This product is GreenTag Green Rate Level A certified as well as low VOC and low Formaldehyde as tested by CETEC based on Greenguard requirements and combines HumiGuard HumiGuard Plus no sag performance with BioBlock paint to inhibit surface growth of mold and mildew.</p> <p>Fine fissured has a NRC of 0.55 and a CAC of 30. Forman also offers Armstrong Fine fissured with High acoustic ratings with a NRC of 0.70 and CAC of 40 for superior performance.</p> 

Manner in which the product may contribute towards points in Green Star NZ	Legend of Symbols in EnviroSpec
• Products must meet specific criteria (e.g. Paint VOC emissions, carpets, etc)	
• Products may help achieve points by their very nature, if they are specified and included in the design in accordance with Green Star NZ requirements (e.g. bicycle racks)	●
• Products may help achieve an outcome but they must be used in a specific manner (e.g. lighting control and zoning systems) <b>OR</b> This product can contribute towards the outcome but many other products or factor influence that same outcome (E.g. Potable Water Calculator)	○

## Disclaimer

### Please read this carefully

Green Star® is a registered trade mark of the Green Building Council of Australia (GBCA), used under licence in New Zealand by the New Zealand Green Building Council (NZGBC). The information represented on EnviroSpec is not endorsed by the GBCA or the NZGBC. For detailed technical information about credit requirements refer to the Green Star® Technical Manuals. Rating Tools and Technical Manuals are subject to change by the NZGBC, and any decision regarding the award of credits towards a Green Star® rating in New Zealand is at the sole discretion of the NZGBC.

EnviroSpec does not accept liability for any loss or damages resulting from the use of this document and emphasizes that this document is provided as guidance only. Use of, or reliance upon, any information contained in this report is at the user's own risk.

The information presented in this report is valid for the Green Star® NZ tools nominated herein only. As and when the NZGBC brings out new Green Star® NZ tools, the information may require updating. EnviroSpec will only update information in this report upon receiving written consent from the Manufacturer, Supplier or upon request from the NZGBC. **It is the responsibility of the reader to check for regular updates.**

Green Star NZ tool	Credit category	Points available <sup>1</sup>	Contribution symbol	Contribution Potential (points) <sup>1</sup>	Detail
<b>Office Design and Built 2009</b>	IEQ - 8	3	○	Contributing factor	This credit rewards buildings that maximize daylight. Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may help improve the floor area with a daylight factor above 2.5%.
	IEQ - 11	3	✔○	2 (Contributing factor)	This credits rewards for good visual comfort and lighting design. To achieve 2 point or more, the light reflectance of Ceilings must be minimum 75%. Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average), thus satisfying this requirement. The remaining items in this credit are based on lighting design and are not product dependent.
	IEQ - 13	2	○	Contributing factor	This credit rewards buildings that maintain adequate noise levels. Armstrong Fine Fissured Ceiling tiles have a CAC of 30 and NRC of 0.55 (40 and 0.70 respectively for the high NRC version) which may assist in maintaining suitable noise levels.
	ENE - 4	3	○	Contributing factor	This credit rewards design options that lessen lighting energy consumption while maintaining adequate lighting levels. Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may assist in reducing the lighting output required to obtain a given lighting level in a space.
	MAT - K	2	✔	2 Points	This credit rewards the use of eco-preferred and/or low VOC/formaldehyde emitting products for ceiling tiles, engineered wood products and gypsum plasterboard. The nominated product is GreenTag Green Rate Level A certified, thus satisfying the full point requirements for ceiling tiles.
<b>Education 2009</b>	IEQ - 8	4	○	Contributing factor	This credit rewards buildings that maximize daylight. Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may help improve the floor area with a daylight factor above 2.5%.
	IEQ - 11	3	✔○	2 (Contributing factor)	This credits rewards for good visual comfort and lighting design. To achieve 2 point or more, the light reflectance of Ceilings must be minimum 75%. Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average), thus satisfying this requirement. The remaining items in this credit are based on lighting design and are not product dependent.
	IEQ - 13	2	○	Contributing factor	This credit rewards buildings that maintain adequate noise levels. Armstrong Fine Fissured Ceiling tiles have a CAC of 30 and NRC of 0.55 (40 and 0.70 respectively for the high NRC version) which may assist in maintaining suitable noise levels.
	MAT - B	3	✔	Up to 3 points (unweighted product calculator score)	<b>When used for Ceiling tiles:</b> * Ceiling tiles without finish required (i.e. Prefinished approved eco-label certified ceiling tiles) = 3 points. ** Ceiling tiles requiring additional paint or finish = 1.5 points (with the additional 1.5 points achievable if the paint/finish also has an approved eco label.)

<b>Industrial 2009</b>	IEQ - 8	4	○	Contributing factor	This credit rewards buildings that maximize daylight. Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may help improve the floor area with a daylight factor above 2.5%.
	IEQ - 11	3	✓○	1 (Contributing factor)	This credits rewards for good visual comfort and lighting design. To achieve 2 point or more, the light reflectance of Ceilings must be minimum 75%. Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average), thus satisfying this requirement. The remaining items in this credit are based on lighting design and are not product dependent.
	IEQ - 13	2	○	Contributing factor	This credit rewards buildings that maintain adequate noise levels. Armstrong Fine Fissured Ceiling tiles have a CAC of 30 and NRC of 0.55 (40 and 0.70 respectively for the high NRC version) which may assist in maintaining suitable noise levels.
	MAT - K	2	✓	2 Points	This credit rewards the use of eco-preferred and/or low VOC/formaldehyde emitting products for ceiling tiles, engineered wood products and gypsum plasterboard. The nominated product is GreenTag Green Rate Level A certified, thus satisfying the full point requirements for ceiling tiles.
<b>Office Interiors 2009</b>	IEQ - 8	3	○	Contributing factor	This credit rewards buildings that maximize daylight. Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may help improve the floor area with a daylight factor above 2.5%.
	IEQ - 11	3	✓○	2 (Contributing factor)	This credits rewards for good visual comfort and lighting design. To achieve 2 point or more, the light reflectance of Ceilings must be minimum 75%. Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average), thus satisfying this requirement. The remaining items in this credit are based on lighting design and are not product dependent.
	IEQ - 13	2	○	Contributing factor	This credit rewards buildings that maintain adequate noise levels. Armstrong Fine Fissured Ceiling tiles have a CAC of 30 and NRC of 0.55 (40 and 0.70 respectively for the high NRC version) which may assist in maintaining suitable noise levels.
	ENE- 4	3	○	Contributing factor	This credit rewards design options that lessen lighting energy consumption while maintaining adequate lighting levels. Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may assist in reducing the lighting output required to obtain a given lighting level in a space.
	MAT - B	7	✓	Up to 7 points (unweighted product calculator score)	<b>When used for Ceiling tiles:</b> * Ceiling tiles without finish required (i.e. Prefinished approved eco-label certified ceiling tiles) = 7 points. ** Ceiling tiles requiring additional paint or finish = 3.5 points (with the additional 3.5 points achievable if the paint/finish also has an approved eco label.)

<sup>1</sup> Points available and points achieved are considered pre-weighting. Final Green Star NZ category weightings for each tool still apply.

<sup>2</sup> Post – September 2013, the NZGBC released updated credit classifications with the VOC/ Formaldehyde emission limits on products now being incorporated into the MAT category.