

ERIS



ERIS with PeakForm 24mm Exposed Tee Grid

BENEFITS

- HumiGuard RH95 performance –Sag-resistant formulation to withstand extreme temperatures up to 49°C and relative humidity up to 95%
- Economical with low maintenance
- Non-directional visual reduces installation time and waste
- Light weight and easy to install on standard PeakForm 24mm grid

APPLICATION AREAS

- Offices
- Healthcare
- Education
- Retail
- Public areas



Inspiring Great Spaces™

Armstrong®
CEILING SYSTEMS

ERIS



RH95
Humidity
Resistant



Recycled Content



Light Reflectance

Panel Options	SQUARE LAY-IN	
	 <p>Prelude 24mm Grid</p>	
1200 x 600 x 9mm	3741EX	



NRC 0.45



RH95%



Conforms with BCA Spec. C1.10 and tested to AS/NZS 3837:1998 – Group 1, AS/NZS 1530.3, ISO 5660 – Group 1 –S



0.39 m²K/W



2.64 kg/m²

Green Star: Potential contribution

MAN	IEQ			ENE	MAT and Mat. Calc.		
Waste Management	Daylight Factor	Noise Levels	Emissions	Energy	Modular & Design for Disassembly	Product Stewardship	Recycled Content
✓	✓	–	✓	✓	✓	✓	✓

Material

Wet-formed mineral fibre

Surface Finish

Factory-applied vinyl latex paint with "BioBlock™" mould/mildew inhibitor"

Backloading Recommendation

Contact your local Armstrong representative

Anti Mould / Mildew & Bacteria

"BioBlock™ Plus" contains an antimicrobial treatment, providing resistance against growth of mold/mildew and Gram-positive and Gram-negative odour/stain causing bacteria.

Suspension Systems

PeakForm Prelude 24mm Steel Grid above, with 'Blue Tongue' Aluminium upon request.



Armstrong World Industries Pty Ltd
www.armstrongceilings.com.au

NSW
Telephone (02) 9748 1588

VIC/TAS
Telephone (03) 9580 9633

QLD/NT
Telephone (07) 3809 5565

©2015 Armstrong World Industries Pty Ltd AWP0315 Printed on Zanders Mega Recycled paper

Inspiring Great Spaces™



CEILING SYSTEMS