

Head Office

Unit 12, 8 Leighton Place
Hornsby
NSW, 2077
Australia

Firefly Office

P.O BOX 52
Laidley
QLD, 4341
Australia

Contact details

Phone: (07) 5411 4209
Mobile: 0400 966 899
Email: trevor@tbafirefly.com.au

MATERIAL DESCRIPTION

PLUS 60 Cavity Fire Barrier is a flexible and lightweight fabric with an inner core of insulating fire protection. Acoustic performance = 46dB room to room

CERTIFICATION

Tested in accordance with:
AS1530.4
BRANZ Report Number FAR1628

For both vertical and horizontal applications

UNIT OF MEASURE

ROLL

SIZE

6m x 1.3m = 7.8m²

WEIGHT

2.2kg per m² 10mm thick

FRL-/120/30

APPLICATIONS

This easy to install flexible fire barrier is used as a fire engineered solution to continue compartment walls up into the roof void, maintaining both the integrity and insulation of the compartmentation between dwellings, lift shafts and stairwells, ideal for but not limited to strata units. Can also be used to provide inside out / outside in fire protection to boundary walls on both steel and timber framed buildings.

Flexibility and fire rating level makes this product perfect for bespoke applications.

OS S S A



Bespoke Application Fire Protection Serpentine Sackler Gallery UK



Callignee II Victoria



SES Building 2012 NSW