



Product Description

Pink® Batts® Silencer® 100mm, 75mm, Handy Pack and MidFloor is a lightweight acoustic insulation specifically designed to be placed in standard stud walls and floors to aid in reducing the transmission of airborne sound between rooms and floors. When installed correctly it will increase the sound barrier properties of the wall or floor by reducing the reverberation of sound resonating within the cavity.

Pink® Batts® Silencer® also possesses good thermal properties. Pink® Batts® Silencer® products are grey in colour to assist specifier on site identification.

Pink® Batts® Silencer® Acoustic Insulation is manufactured in plants with AS/NZS ISO 9001 certification. The manufacturing process is continually quality controlled to produce product to assured high standards.

New Zealand Building Code (NZBC, B2, F2, G6)

The Pink® Batts® Silencer® range will satisfy the requirements of NZBC Clause B2.3(b) 50 years durability when used in dry, protected construction cavities. The Pink® Batts® Silencer® range will meet the relevant requirements of NZBC F2 Hazardous Building Materials and G6 Airborne & Impact Sound.

Product	Thickness (mm)	Pieces per Bale	Piece Size (mm)	Area per Bale (m ²)	Thermal Conductivity	R-value (m ² K/W)	NRC
Pink® Batts® Silencer® 100mm	100	20	1140 x 580	13.2	.0395 W/m	2.4	1.04
Pink® Batts® Silencer® Handy Pack	100	20	580 x 482	5.0	.0395 W/m	2.4	1.04
Pink® Batts® Silencer® MidFloor	150	10	1140 x 432	4.9		3.6	1.10
Pink® Batts® Silencer® 75mm	75	26	1140 x 580	17.2		1.9	.91